

ANTI BANDIT MAGNETIC LOCKING MEDIUM RISK DOORS





ITAS ANTI BANDIT MAGNETIC LOCKING MEDIUM RISK DOORS

•Aesthetically pleasing, robust secure emergency exit door that can also regulate pedestrians and goods with minimum delay and inconvenience to and from secure areas, during an effective life expectancy of at least 10 years, subject to normal usage and maintenance.

SUITABLE FOR

- •Medium risk and vulnerable areas at Banks, Cash Centres, Embassies, Mines, Prisons, Hospitals, Commercial, Government and Financial etc institutions.
- •Medium risk Control rooms and Data centres.
- •Medium risk Emergency Exit facilities.

STRUCTURE FEATURES AND CONTROLS

- •Mild steel with industrial primer coated finish
- Optical door viewer
- •To comply with SANS requirements when utilised as Emergency Exit Doors:-
- •800mm wide clear opening for an occupancy of not more than 25 persons,
- •1200mm wide for buildings erected before 2011 with occupancy not more than 100 persons
- •1500mm wide for buildings erected after 2011 with occupancy of not more than 100 persons.
- •Demounting and re-using as often as required
- •Secured with heavy duty 500kg pull resistant magnetic lock with secure emergency mechanical key override and control facilities and electronic override button provided 1200mm from floor level on secure side for emergency evacuation purpose and to override the electronic system in the event of total power or electronic system failure
- ·Standard handgun and ammo resistant

- •Sound and temperature resistant.
- •LED's to indicate state of 220V power source and emergency supply battery

OPTIONAL EXTRAS

- •Remote control and monitoring of above facilities
- Secure door position monitoring and control
- •Secure door alarm contacts
- •Interface with all reputable building management systems with positive bio-metric fingerprint entry and exit identification with audit trail etc facilities.
- •AK 47 and R1 Rifle resistant.
- •Powder coating and other final finishes to suit individual requirements.
- •BR Glass view panel with internal hinged cover.

DIMENSIONS	
800 Door:	
Clear Emergency Exit Opening:	800mm (w) x 2000mm (h)
Outside:	1100mm (w) x 2360mm (h)
Wall opening required:	1150mm (w) x 2400mm (h)
1200 Door:	
Clear Emergency Exit Opening:	1200mm (w) x 2000mm (h)
Outside:	1500mm (w) x 2360mm (h)
Wall opening required:	1550mm (w) x 2400mm (h)
1500 Door:	
Clear Emergency Exit Opening	1500mm (w) x 2000mm (h)
Outside:	1800mm (w) x 2300mm (h)
Wall opening required:	1850mm (w) x 2400mm (h)

DATA	
Power Supply requirements:	Clean constant 220 V AC 15amp
Emergency Power Supply Provided:	17Amp hour rechargeable battery supply
Compliant:	SANS, 10, 400 "A, S &T"
Credentials	Agrément Certificate 2015/479

