

SMALLFOOT ANTI-HOSTAGE MANTRAP MKII







ITAS SMALL FOOT MANTRAP DOOR MKII

•Aesthetically pleasing, user-friendly, compact, robust secure single person entry and exit door to regulate pedestrians and goods with minimum delay and inconvenience to and from secure areas, during an effective life expectancy of at least 10 years, subject to normal usage and maintenance.

SUITABLE FOR

- •High risk and vulnerable entrances at Banks, Cash Centres, Embassies, Mines, Prisons, Hospitals, Commercial, Government and Financial etc institutions.
- •Control rooms and Data centres.
- Emergency Exits

STRUCTURE FEATURES AND CONTROLS

- •Industrial primer coated mild steel construction.
- •Accommodates extra-large, claustrophobic persons, wheelchairs, trolleys, bulk items, and fire etc emergency evacuation situations without the need of an adjacent emergency exit door.
- •Secure door position monitoring, control and door alarm contacts
- •LED electronic fault finding diagnostic for easy fault finding
- •LED AC power and emergency battery status indicator
- •Costly floor space savings achieved with the small footprint

- •Fits into standard door openings with minor modifications as well as pass through standard doorways, passages, lifts etc to facilitate installations at various venues.
- •Dismantled, refurbished and re-used as often as required, whilst handling continuous high volume traffic
- •Discourages hold-up, hostage and tailgating situations.

OPTIONAL EXTRAS

- •Electronic beam detection, enhanced with horizontal hip high and a lower set of infrared curtains consisting of 3 transmitters and 3 responding receivers each inside the cubicle, time delay overrides unlocking and override restriction features with an applicable warning notice fixed to the outside of the unit
- •Remote control and monitoring of above facilities.
- •Interface with all reputable building management systems incorporating technology such as Bio metric readers with audit trail facilities.
- •Facilities for Pin Lens cameras behind full length opaque lenses.
- •Ballistic levels up to AK 47 and R1 rifles.
- •Special Powder coating or final finish to suit individual requirements.

DIMENSIONS	
External:	1105mm (w) x 810mm (d) x 2305mm (h)
Internal Mantrap Mode:	560mm (w) x 600mm (d) x 2000mm (h)
Bulk Goods etc:	825mm (w) x 800mm (d) x 2000mm (h)
Emergency Exit Mode:	825mm (w) x 800mm (d) x 2000mm (h)
Clear opening required to build in Unit:	1120mm (w) x 810mm (d) x 2330mm (h)

DATA	
Power Supply requirements:	Clean constant 220 V AC 15amp
Emergency Power Supply Provided:	7Amp hour rechargeable battery supply
Compliant:	SANS, 10, 400 "A, S &T"
Credentials	Agrément Certificate 2015/479

